

according to 1907/2006/EC, Article 31

Fast Cast Natural - RESIN

Revision Date: 11.03.2025

Revision: 1 Supersedes Date: N/A

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : FastCast Natural - RESIN

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Art & Craft making

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Eli-Chem Resins UK Ltd

212 Dunsfold Park, Canada Avenue Cranleigh, Surrey GU6 8GA (UK)

Telephone : +44 (0) 1483 266636 E-mail address of person : sales@elichem.co.uk

responsible for the SDS

1.4 Emergency telephone number

Emergency Contact : +44 (0) 1483 266636 (Office Hours Only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.



according to 1907/2006/EC, Article 31

Fast Cast Natural - RESIN

Revision Date: 11.03.2025

Revision: 1 Supersedes Date: N/A

Page 2 of 11

P337 + P313 If eye irritation persists: Get medical advice/ attention.

Additional Labelling:

EUH208 Contains 4-morpholinecarbaldehyde. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]				
Alkyl amino polyoxyalkylenol	Eye Irrit.2; H319	>= 40 - < 60				
25214-63-5						
500-035-6						
propylene carbonate	Eye Irrit.2; H319	>= 5 - < 10				
108-32-7						
203-572-1						
01-2119537232-48-XXXX						
4-morpholinecarbaldehyde	Skin Sens.1; H317	< 1				
4394-85-8						
224-518-3						
01-2119987993-12-XXXX						
Substances with a workplace exposure limit :						
hydrocarbons, C12-C15, n-alcane, isoalcane, <2% aro-	Asp. Tox.1; H304	>= 5 - < 10				
matic						
64742-47-8						
920-107-4						
265-149-8						
01-2119453414-43-XXXX						
For the full took of the LLOtetowards would be added this Occident						

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.



according to 1907/2006/EC, Article 31

Fast Cast Natural - RESIN

Revision Date: 11.03.2025

Revision: 1 Supersedes Date: N/A

Page **3** of **11**

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Excessive lachrymation

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and

the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-

ucts

: No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.



according to 1907/2006/EC, Article 31

Fast Cast Natural - RESIN

Revision Date: 11.03.2025

Revision: 1 Supersedes Date: N/A

Page 4 of 11

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in

accordance with local regulations.

Storage class (TRGS 510) : 10, Combustible liquids

Other data : No decomposition if stored and applied as directed.



according to 1907/2006/EC, Article 31

Fast Cast Natural - RESIN

Revision Date: 11.03.2025

Revision: 1 Supersedes Date: N/A

Page **5** of **11**

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters *	Basis *
hydrocarbons, C12-C15, n-alcane, isoalcane, <2% aromatic	64742-47-8	AGW	600 mg/m3	DE TRGS 900

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved

standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer

specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe working

limits of the selected respirator.

organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods



according to 1907/2006/EC, Article 31

Fast Cast Natural - RESIN

Revision Date: 11.03.2025 Revision: 1

Supersedes Date: N/A

Page **6** of **11**

for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : various

Odour : characteristic

Odour Threshold : No data available

Flash point : > 101 °C

Autoignition temperature : No data available

Decomposition temperature : No data available

Lower explosion limit (Vol-%) : No data available

Upper explosion limit (Vol-%) : No data available

Flammability : No data available

Explosive properties : No data available

Oxidizing properties : No data available

pH : Not applicable

Melting point/range / Freez-

ing point

No data available

Boiling point/boiling range : No data available

Vapour pressure : 0,04 hPa

Density : ca.1,02 g/cm3

at 20 °C

Water solubility : insoluble



according to 1907/2006/EC, Article 31

Fast Cast Natural - RESIN

Revision Date: 11.03.2025 Revision: 1

Supersedes Date: N/A Page **7** of **11**

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic

: ca.70 mPa.s at 25 °C

Viscosity, kinematic

: > 20,5 mm2/s at 40 °C

Relative vapour density

: No data available

Evaporation rate

: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

Alkyl amino polyoxyalkylenol:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.



according to 1907/2006/EC, Article 31

Fast Cast Natural - RESIN

Revision Date: 11.03.2025

Revision: 1 Supersedes Date: N/A

Page 8 of 11

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Alkyl amino polyoxyalkylenol:

Toxicity to fish : LC50: > 100 mg/l, 96 h, Fish

Toxicity to daphnia and other

aquatic invertebrates

: EC50: > 100 mg/l, 48 h, Daphnia (water flea)

Toxicity to algae : EC50: > 100 mg/l, 72 h, Desmodesmus subspicatus (green

algae)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or



according to 1907/2006/EC, Article 31

Fast Cast Natural - RESIN

Revision Date: 11.03.2025

Revision: 1 Supersedes Date: N/A

Page 9 of 11

very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with the EWC Waste Regulation the

classification of waste is to be assigned to the jurisdiction of the origin of waste. Therefore, it is not possible to assign a

particular waste identification number.

Completely emptied packagings may be given for recycling. Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

SECTION 14: Transport information

ADR

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

: Banned and/or restricted

(low boiling point modified naphtha)



according to 1907/2006/EC, Article 31

Fast Cast Natural - RESIN

Revision Date: 11.03.2025

Revision: 1 Supersedes Date: N/A

Page **10** of **11**

preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

REACH Information: All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

preregistered or registered by us, and/or
excluded from the regulation, and/or
exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water contaminating class

(Germany)

: WGK 1 slightly water endangering

VOC-CH (VOCV) : 0,33 %

no VOC duties

VOC-EU (solvent) : 15,28 %

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Full text of other abbreviations

Asp. Tox. Aspiration hazard Eye Irrit. Eye irritation Skin Sens. Skin sensitisation

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route Chemical Abstracts Service

CAS Chemical Abstracts Service
DNEL Derived no-effect level

EC50 Half maximal effective concentration GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)



according to 1907/2006/EC, Article 31

Fast Cast Natural - RESIN

Revision Date: 11.03.2025

Revision: 1 Supersedes Date: N/A

Page 11 of 11

LC50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships,

1973 as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic PNEC Predicted no effect concentration

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

SVHC Substances of Very High Concern vPvB Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



according to 1907/2006/EC, Article 31

Revision Date: 11.03.2025 Revision: 1

> Supersedes Date: N/A Page 1 of 13

Fast Cast Natural - HARDENER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : FastCast Natural - HARDENER

Relevant identified uses of the substance or mixture and uses advised against

Product use : Art & Craft making

1.2 Details of the supplier of the safety data sheet

Company name of supplier : Eli-Chem Resins UK Ltd

212 Dunsfold Park, Canada Avenue Cranleigh, Surrey GU6 8GA (UK)

Telephone : +44 (0) 1483 266636 E-mail address of person : sales@elichem.co.uk

responsible for the SDS

1.3 Emergency telephone number

Emergency Contact : +44 (0) 1483 266636 (Office Hours Only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H332: Harmful if inhaled.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Carcinogenicity, Category 2 H351: Suspected of causing cancer.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure if inhaled.

Chronic aquatic toxicity, Category 1 H410: Very toxic to aquatic life with long lasting

effects.



according to 1907/2006/EC, Article 31

Revision Date: 11.03.2025

Revision: 1 Supersedes Date: N/A

Page **2** of **13**

Fast Cast Natural - HARDENER

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H410

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

May cause respiratory irritation

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Very toxic to aquatic life with long lasting

effects.

Precautionary statements : **Prevention:**

P201 Obtain special instructions before use.
P260 Do not breathe dust/ fume/ gas/ mist/

vapours/ spray.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

P284 In case of inadequate ventilation wear

respiratory protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel

unwell.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Hazardous components which must be listed on the label:

• 9016-87-9 Diphenylmethanediisocyanate, isomeres and homologues

Additional Labelling:

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



according to 1907/2006/EC, Article 31

Revision Date: 11.03.2025 Revision: 1

> Supersedes Date: N/A Page 3 of 13

Fast Cast Natural - HARDENER

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Diphenylmethanediisocyanate, isomeres and homologues 9016-87-9	Acute Tox.4; H332 Skin Irrit.2; H315 Eye Irrit.2; H319 Resp. Sens.1; H334 Skin Sens.1; H317 Carc.2; H351 STOT SE3; H335 STOT RE2; H373	>= 60 - < 80
bis(isopropyl)naphthalene 38640-62-9 254-052-6 01-2119565150-48-XXXX	Asp. Tox.1; H304 Aquatic Chronic1; H410	>= 25 - < 40

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed



according to 1907/2006/EC, Article 31

Revision Date: 11.03.2025 Revision: 1

> Supersedes Date: N/A Page **4** of **13**

Fast Cast Natural - HARDENER

Symptoms : Asthmatic appearance

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Erythema Headache Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficulties

if inhaled.

May cause respiratory irritation. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

: No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in

accordance with local regulations.



according to 1907/2006/EC, Article 31 Fast Cast Natural - HARDENER

Revision Date: 11.03.2025 Revision: 1

> Supersedes Date: N/A Page 5 of 13

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel, Methods for cleaning up

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

: Avoid formation of aerosol. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures

when handling chemical products

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures

: Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in

accordance with local regulations.



according to 1907/2006/EC, Article 31

Revision Date: 11.03.2025 Revision: 1

> Supersedes Date: N/A Page 6 of 13

Fast Cast Natural - HARDENER

Storage class (TRGS 510) : 10, Combustible liquids

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parame- ters *	Basis *
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	AGW	0,05 mg/m3	DE TRGS 900

8.2 Exposure controls

Personal protective equipment

Eye protection Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow

manufacturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (0,4 mm), Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe working

limits of the selected respirator.



according to 1907/2006/EC, Article 31

Revision Date: 11.03.2025 Revision: 1

> Supersedes Date: N/A Page **7** of **13**

Fast Cast Natural - HARDENER

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 -Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : brown

Odour : characteristic

Odour Threshold : No data available

Flash point : > 101°C

Autoignition temperature : No data available

Decomposition temperature : No data available

Lower explosion limit (Vol-%) : No data available

Upper explosion limit (Vol-%) : No data available

Flammability : No data available

Explosive properties : No data available

Oxidizing properties : No data available

pH : Not applicable

Melting point/range / Freez-

ing point

No data available



according to 1907/2006/EC, Article 31

Revision Date: 11.03.2025 Revision: 1

> Supersedes Date: N/A Page 8 of 13

Fast Cast Natural - HARDENER

Boiling point/boiling range : No data available

Vapour pressure : 0,01 hPa

Density : ca.1,14 g/cm3

at 20°C

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20,5 mm2/s

at 40°C

Relative vapour density : No data available

Evaporation rate : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Avoid moisture.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if inhaled.

Components:



according to 1907/2006/EC, Article 31

Revision Date: 11.03.2025 Revision: 1

Supersedes Date: N/A

Page 9 of 13

Fast Cast Natural - HARDENER

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

bis(isopropyl)naphthalene:

Acute oral toxicity : LD50 Oral (Rat): > 3.900 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,64 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 4.500 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available



according to 1907/2006/EC, Article 31

Revision Date: 11.03.2025 Revision: 1

> Supersedes Date: N/A Page **10** of **13**

Fast Cast Natural - HARDENER

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with the EWC Waste Regulation the

classification of waste is to be assigned to the jurisdiction of the origin of waste. Therefore, it is not possible to assign a

particular waste identification number.

Completely emptied packagings may be given for recycling. Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

SECTION 14: Transport information

ADR

14.1 UN number : 3082

14.2 Description of the goods : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (bis(isopropyl)naphthalene)

14.3 Class: 914.4 Packing group: IIIClassification Code: M6



according to 1907/2006/EC, Article 31

Revision Date: 11.03.2025 Revision: 1

Supersedes Date: N/A

Page **11** of **13**

Fast Cast Natural - HARDENER

: 9 Labels Tunnel restriction code : (-) 14.5 Environmentally hazard-: yes

IATA

14.1 UN number : 3082

Description of the goods : Environmentally hazardous substance, liquid, n.o.s. bis(isopropyl)naphthalene)

14.2

14.3 Class : 9 14.4 Packing group : 111 : 9 Labels 14.5 Environmentally hazard-: yes

ous

IMDG

14.1 UN number : 3082

14.2 Description of the goods ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (bis(isopropyl)naphthalene)

14.3 Class 14.4 Packing group Ш Labels 9 EmS Number 1 F-A EmS Number 2 : S-F 14.5 Marine pollutant : yes

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: Banned and/or restricted (Diphenylmethanediisocyanate, isomeres and homologues)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

REACH Information: All substances contained in our Products are

- preregistered or registered by our upstream suppliers, and/or

- preregistered or registered by us, and/or



according to 1907/2006/EC, Article 31

Revision Date: 11.03.2025 Revision: 1

> Supersedes Date: N/A Page **12** of **13**

Fast Cast Natural - HARDENER

- excluded from the regulation, and/or

- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E1 Quantity 1 Quantity 2 ENVIRONMENTAL 100 t 200 t

HAZARDS

Water contaminating class

(Germany)

: WGK 3 highly water endangering

VOC-CH (VOCV) : no VOC duties

VOC-EU (solvent) : Not applicable

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if in-

haled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure

if inhaled.

H410 Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. Acute toxicity

Aquatic Chronic
Asp. Tox.
Carc.
Carc.
Carcinogenicity
Eye Irrit.
Chronic aquatic toxicity
Aspiration hazard
Carcinogenicity
Eye irritation

Resp. Sens. Respiratory sensitisation

Skin Irrit. Skin irritation
Skin Sens. Skin sensitisation

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

ADR Accord européen relatif au transport international des marchandises

Dangereuses par Route

CAS Chemical Abstracts Service DNEL Derived no-effect level



according to 1907/2006/EC, Article 31

Revision Date: 11.03.2025 Revision: 1

> Supersedes Date: N/A Page **13** of **13**

Fast Cast Natural - HARDENER

EC50 Half maximal effective concentration
GHS Globally Harmonized System

IATA International Air Transport Association

IMDG International Maritime Code for Dangerous Goods

LD50 Median lethal dosis (the amount of a material, given all at once, which

causes the death of 50% (one half) of a group of test animals)

LC50 Median lethal concentration (concentrations of the chemical in air that

kills 50% of the test animals during the observation period)

MARPOL International Convention for the Prevention of Pollution from Ships,

1973 as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic PNEC Predicted no effect concentration

REACH Regulation (EC) No 1907/2006 of the European Parliament and of the

Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

European Chemicals Agency

SVHC Substances of Very High Concern vPvB Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.