



### Product information

Water borne silicone free polishing compound designed to quickly and permanently remove sanding scratches from P1500 and finer on all types of surfaces, depending on polishing pad.

### Product advantages

- Premium all round polish compound
- One compound solution
- Silicone free



### Surfaces

- Clear coats
- Top coats
- Polycarbonate
- Acrylic surfaces
- Solid surfaces
- Gelcoats

### Polishing machine

- Rotating 800 – 2000 rpm
- Random orbital polisher 6000-10000 rpm

### Polishing pad

- Natural lambswool
- Yellow lambswool pro
- Yellow foam pad
- Orange foam pad

### Product properties

Speed:

Polish, gloss:

### Work instruction

1. Shake or stir polishing compound before use
2. Do not use too much compound at a time. Use a small amount which is consumed on a focused area - less messing and clean up!
3. Clean thoroughly before and after polishing
4. Work focused on an area of 40x40 cm at a time
5. Polish until a scratch free surface is achieved
6. Keep the pad clean, a dirty pad causes deep swirls and scratches

### Technical specifications

Density: 1,05 kg/l  
Viscosity: 20,5 Pas  
Colour: White  
pH: 7 - 8

### Storage recommendations

Recommended storage temperature:  
5° - 35° C / 41° - 95° F  
Keep from freezing