

according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - RESIN

Revision Date: 05.08.2024 Revision: 1

Supersedes Date: N/A

Page: 1 / 12

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

SuperCast™ - RESIN

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses

Artwork and decorative applications.

1.3 Details of the supplier of the safety data sheet

Supplier: Eli-Chem Resins UK Ltd

212 Dunsfold Park Canada Avenue Cranleigh GU6 8GA (UK)

+44 (0)1483 266636 (09:00 - 17:00 Mon-Thur / 09:00 - 16:00 Fri)

sales@elichem.co.uk

1.4 Emergency telephone number

Emergency number: +44 (0)1483 266636 office hours only

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Skin Irrit. 2; H315 - Skin corrosion/irritation: Category 2; Causes skin irritation.

Eye Irrit. 2; H319 - Serious eye damage/eye irritation: Category 2; Causes serious eye irritation.

Skin Sens. 1; H317 - Skin sensitisation: Category 1; May cause an allergic skin reaction.

Aquatic Chronic 2; H411 - Hazardous to the aquatic environment: Chronic 2; Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms





Environment (GHS09) · Exclamation mark (GHS07)

Signal word

Warning

Hazard components for labelling

bis-[4-(2,3-epoxipropoxi)phenyl]propane; cas no.: 1675-54-3 oxirane, mono[(c12-14-alkyloxy)methyl] derivs; cas no.: 68609-97-2

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash ... thoroughly after handling.



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - RESIN

Revision Date: 05.08.2024 Revision: 1

Supersedes Date: N/A Page: 2 / 12

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P391 Collect spillage.

Special rules for supplemental label elements for certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Adverse human health effects and symptoms

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH:

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH:

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; REACH No.: 01-2119456619-26-xxxx; EC No.: 216-823-5; CAS No.: 1675-54-3

Weight fraction : $\geq 80 - < 100 \%$

Classification 1272/2008 [CLP]: Skin Irrit. 2; H315 Skin Sens. 1B; H317 Eye Irrit. 2; H319 Aquatic Chronic 2; H411

Specific Conc. Limits : Eye Irrit. 2 ; H319: $C \ge 5$ % • Skin Irrit. 2 ; H315: $C \ge 5$ %

OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS; REACH No.: 01-2119485289-22-0015; EC No.: 271-846-8; CAS

No.: 68609-97-2

Weight fraction : \geq 5 - < 20 %

Classification 1272/2008 [CLP]: Skin Irrit. 2; H315 Skin Sens. 1; H317

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove contaminated, saturated clothing immediately. Wash thoroughly the body (shower or bath). Remove affected person from the danger area and lay down. Transport affected person in lying position, in case of shortness of breath in half-sitting position. Put victim at rest, cover with a blanket and keep warm. Do not leave affected person unattended.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - RESIN

Revision Date: 05.08.2024 Revision: 1

> Supersedes Date: N/A Page: 3 / 12

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. In case of skin reactions, consult a physician. In case of skin irritation, consult a physician.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

Following ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Irritating to eyes and skin.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Extinguishing powder alcohol resistant foam Water spray jet Water

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2) Hydrogen chloride (HCl)

5.3 Advice for firefighters

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Use personal protection equipment. See protective measures under point 7 and 8.

For emergency responders

Use personal protection equipment. Provide adequate ventilation. Remove persons to safety. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3 Methods and material for containment and cleaning up

For containment

Cover drains. Stop leak if safe to do so. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Take up mechanically, placing in appropriate containers for disposal.

For cleaning up

Collect in closed and suitable containers for disposal. Clean contaminated articles and floor according to the environmental legislation.



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - RESIN

Revision Date: 05.08.2024 Revision: 1

> Supersedes Date: N/A Page: 4 / 12

6.4 Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

It is recommended to design all work processes always so that the following is excluded: Inhalation of vapours or spray/mists Skin contact Eye contact

Wear personal protection equipment (refer to section 8). If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Measures to prevent fire

Keep away from sources of ignition - No smoking. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Environmental precautions

Shafts and sewers must be protected from entry of the product. Provide for retaining containers, e.g. floor pan without outflow.

Advices on general occupational hygiene

Working places should be designed to allow cleaning at any time. Floors, walls and other surfaces in the hazard area must be cleaned regularly. After use replace the closing cap immediately. Wash hands and face before breaks and after work and take a shower if necessary. Wash hands before eating, drinking or smoking. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Only use containers specifically approved for the substance/product. Protect containers against damage. Keep container tightly closed and in a well-ventilated place.

Packaging materials

Unsuitable container/equipment material: Copper Alloy, containing copper

Hints on joint storage

Storage class (TRGS 510): 10

Keep away from

Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

DNEL-/PNEC-values

DNEL/DMEL

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; CAS No.: 1675-54-3 Limit value type: DNEL Consumer (systemic)

Exposure route: Dermal
Exposure frequency: Short-term
Limit value: 3,6 mg/kg

Limit value type : DNEL Consumer (systemic)

Exposure route: Dermal
Exposure frequency: Long-term
Limit value: 3,6 mg/kg

Limit value type : DNEL Consumer (systemic)

Exposure route: Inhalation



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - RESIN

Revision Date: 05.08.2024 Revision: 1 Supersedes Date: N/A

Page: 5 / 12

Exposure frequency: Short-term Limit value: 0,75 mg/m³

Limit value type: **DNEL Consumer (systemic)**

Exposure route: Inhalation Exposure frequency: Long-term 0,75 mg/m³ Limit value:

Limit value type: DNEL worker (systemic)

Exposure route: Dermal Exposure frequency: Short-term Limit value: 8,3 mg/kg

DNEL worker (systemic) Limit value type:

Exposure route: Dermal Exposure frequency: Long-term Limit value: 8,3 mg/kg

Limit value type: DNEL worker (systemic)

Exposure route: Inhalation Exposure frequency: Short-term Limit value: 12,3 mg/m³

DNEL worker (systemic) Limit value type:

Exposure route: Inhalation Exposure frequency: Long-term 12,3 mg/m³ Limit value:

OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS; CAS No.: 68609-97-2

Limit value type: DNEL Consumer (systemic)

Exposure route: Inhalation Exposure frequency: Long-term 0,87 mg/m³ Limit value:

Limit value type: **DNEL Consumer (systemic)**

Exposure route: Dermal Exposure frequency: Long-term Limit value: 0,5 mg/kg bw/day

Limit value type: **DNEL Consumer (systemic)**

Exposure route: Oral Exposure frequency: Long-term Limit value: 0,5 mg/kg bw/day Limit value type: DNEL worker (systemic)

Exposure route: Dermal Exposure frequency: Long-term Limit value: 1 mg/kg bw/day DNEL worker (systemic) Limit value type:

Inhalation Exposure route: Exposure frequency: Long-term Limit value: 3,6 mg/m³

PNEC

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; CAS No.: 1675-54-3 PNEC (Aquatic, freshwater) Limit value type:

Limit value: 0,006 mg/l

PNEC (Aquatic, intermittent release) Limit value type:

Limit value: 0,018 mg/l

PNEC (Aquatic, marine water) Limit value type:

Limit value: 0,0006 mg/l

Limit value type : PNEC (Sediment, freshwater)

0,996 mg/l Limit value:

PNEC (Sediment, marine water) Limit value type:

Limit value: 0,0996 mg/l Limit value type: PNEC (Soil)



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - RESIN

Revision Date: 05.08.2024 Revision: 1

> Supersedes Date: N/A Page: 6 / 12

Limit value: 0,196 mg/l

Limit value type : PNEC (Sewage treatment plant)

Limit value : 10 mg/l

OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS; CAS No.: 68609-97-2

Limit value type : PNEC (Aquatic, freshwater)

Limit value : 0,106 mg/l

Limit value type : PNEC (Aquatic, marine water)

Limit value: 0,011 mg/l

Limit value type : PNEC (Sediment, freshwater)

Limit value: 307,2 mg/kg

Limit value type : PNEC (Sediment, marine water)

Limit value : 30,72 mg/kg
Limit value type : PNEC (Soil)
Limit value : 1,234 mg/kg

Limit value type : PNEC (Sewage treatment plant)

Limit value: 10 mg/l

8.2 Exposure controls

Appropriate engineering controls

Provide for sufficient ventilation. Technical measures and the application of suitable work processes have priority over personal protection equipment.

Personal protection equipment

Eye/face protection

Suitable eye protection

Eye glasses with side protection DIN-/EN-Norms: EN 166

Provide eye shower and label its location conspicuously

Skin protection

Hand protection

Suitable gloves type : Gloves with long cuffs

Suitable material: NBR (Nitrile rubber) PVC (polyvinyl chloride) CR (polychloroprene, chloroprene rubber) Butyl

caoutchouc (butyl rubber) FKM (fluoro rubber)

Wearing time with occasional contact (splashes) : > 10 min

Wearing time with permanent contact: > 480 min

Remark: When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Breakthrough times and swelling properties of the material must be taken into consideration.

Tested protective gloves must be worn

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

DIN-/EN-Norms: EN ISO 374

Body protection

Suitable protective clothing

Remark : DIN-/EN-Norms

Protective clothing. : EN 14605 footwear : EN ISO 20345

Breakthrough times and swelling properties of the material must be taken into consideration.

Only wear fitting, comfortable and clean protective clothing.

Respiratory protection

Usually no personal respirative protection necessary. Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation insufficient exhaust

Suitable respiratory protection apparatus

Combination filtering device Filter type: A



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - RESIN

Revision Date: 05.08.2024 Revision: 1

Supersedes Date: N/A

Page: 7 / 12

Remark

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

General information

When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Wash contaminated clothing immediately. Wash hands before breaks and after work. Emergency shower installed

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Liquid
Colour: light yellow
Odour: characteristic
Safety characteristics

Freezing point: (1013 hPa) No data available
Initial boiling point and boiling

range: (1013 hPa) > 200 °C

Decomposition temperature :(1013 hPa)No data availableFlash point :100 °C

Auto-ignition temperature :No data availableLower explosion limit :No data availableUpper explosion limit :No data availableVapour pressure :(50 °C)not determined

Density: (25 °C) 1,14 g/cm³

Relative density: (20 °C) No data available

Water solubility: (20 °C) No data available

pH: No data available log P O/W: No data available

 Flow time :
 (20 °C)
 No data available
 DIN-cup 4 mm

 Viscosity :
 (25 °C)
 approx.
 3000
 mPa*s

Odour threshold :No data availableRelative vapour density :(20 °C)No data available

VOC-value : 0 g/l **Flammable solids :** Not applicable.

Flammable gases: Not applicable.

9.2 Other information

practically insoluble : Water **Other safety characteristics**

Evaporation rate

No data available

Miscibility

No data available

Conductivity

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

The product is stable under storage at normal ambient temperatures.

10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - RESIN

Revision Date: 05.08.2024 Revision: 1

Supersedes Date: N/A

Page: 8 / 12

Violent reaction with: Amines. Acid

10.4 Conditions to avoid

Keep away from heat.

10.5 Incompatible materials

Oxidising agent, strong. Strong acid Amines.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Acute oral toxicity

Parameter: LD50 (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; CAS No.: 1675-54-3)

Exposure route: Oral Species: Rat

Effective dose: > 15000 mg/kg

Parameter: LD50 (OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS; CAS No.: 68609-97-2)

Exposure route : Oral Species : Rat

Effective dose : > 2000 mg/kg bw/day

Acute dermal toxicity

Parameter: LD50 (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; CAS No.: 1675-54-3)

Exposure route: Dermal
Species: Rabbit
Effective dose: 23000 mg/kg

Parameter: LD50 (OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS; CAS No.: 68609-97-2)

Exposure route : Dermal Species : Rat

Effective dose : > 4000 mg/kg bw/day

Corrosion

Product characteristics: Irritating to eyes and skin.

Skin corrosion/irritation

Product characteristics: Irritating to skin.

Serious eye damage/eye irritation

Product characteristics: Irritating to eyes.

Respiratory or skin sensitisation

Kespiratory or SKIN S Skin sensitisation

Product characteristics: May cause an allergic skin reaction.

Sensitisation to the respiratory tract

No data available

Repeated dose toxicity (subacute, subchronic, chronic)

Subacute dermal toxicity

Parameter: NOAEL(C) (OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS; CAS No.:

68609-97-2)

Exposure route : Dermal Species : Rat

Effective dose: 100 mg/kg bw/day

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Overall assessment on CMR properties



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - RESIN

Revision Date: 05.08.2024 Revision: 1

Supersedes Date: N/A

Page: 9 / 12

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH:

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter: LC50 (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; CAS No.: 1675-54-3)

Species: Oncorhynchus mykiss (Rainbow trout)

Effective dose : 2 mg/l Exposure time : 96 h

Parameter: LC50 (OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS; CAS No.: 68609-97-2)

Species: Oncorhynchus mykiss (Rainbow trout)

Effective dose : > 100 mg/l Exposure time : 96 h Acute (short-term) toxicity to crustacea

Parameter: EC50 (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; CAS No.: 1675-54-3)

Species: Daphnia magna (Big water flea)

Effective dose : 1,8 mg/l Exposure time : 48 h

Parameter: EC50 (OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERIVS; CAS No.: 68609-97-2)

Species: Daphnia magna (Big water flea)

Effective dose: 1 - 10 mg/l Exposure time: 48 h

Chronic (long-term) toxicity to aquatic invertebrate

Parameter: NOEC (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; CAS No.: 1675-54-3)

Species: Daphnia magna (Big water flea)

Effective dose : 0,55 mg/l Exposure time : 21 day(s)

Acute (short-term) toxicity to algae and cyanobacteria

Parameter: EC50 (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; CAS No.: 1675-54-3)

Species : Selenastrum capricornutum

Effective dose : 11 mg/l Exposure time : 72 h

Toxicity to microorganisms

Parameter : EC50 (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE ; CAS No. : 1675-54-3)

Effective dose : > 42,6 mg/l Exposure time : 8 h

12.2 Persistence and degradability



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - RESIN

Revision Date: 05.08.2024 Revision: 1

Supersedes Date: N/A Page: 10 / 12

.

Biodegradation

Parameter: Biodegradation (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; CAS No.: 1675-54-3)

Degradation rate : 12 %
Test duration : 28 day(s)

Evaluation : Not readily biodegradable (according to OECD criteria)

Method: OECD 302B

12.3 Bioaccumulative potential

Parameter: Bioconcentration factor (BCF) (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; CAS No.

: 1675-54-3)

Value : 100 - 3000

Parameter: Partition coefficient n-octanol/water (log value) (BIS-[4-(2,3-

EPOXIPROPOXI)PHENYL]PROPANE; CAS No.: 1675-54-3)

Value : 3,242

12.4 Mobility in soil

Adsorption

Parameter: Mobility in soil (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE; CAS No.: 1675-54-3)

Effective dose : 500 - 2000 pOC

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH:

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of waste according to applicable legislation. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Collect the waste separately. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

14.1 UN number or ID number

UN 3082

14.2 UN proper shipping name

Land transport (ADR/RID)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

Sea transport (IMDG)

 ${\tt ENVIRONMENTALLY\ HAZARDOUS\ SUBSTANCE,\ LIQUID,\ N.O.S.\quad ({\tt EPOXY\ RESIN})}$

Air transport (ICAO-TI / IATA-DGR)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es): 9
Classification code: M6
Hazard identification number (Kemler
No.): 90



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - RESIN

Revision Date: 05.08.2024 Revision: 1 Supersedes Date: N/A

Page: 11 / 12

Tunnel restriction code :

Special Provisions : LQ $5 \cdot E1 \cdot ADR : -(SP 375 \le 5 \cdot kg)$

Hazard label(s): 9 / N

Sea transport (IMDG)

Class(es):

EmS-No.: F-A / S-F

Special Provisions : LQ 5 $I \cdot E 1 \cdot IMDG : -(SP 2.10.2.7 \le 5 I/kg)$

Hazard label(s): 9 / N

Air transport (ICAO-TI / IATA-DGR)

Class(es):

Special Provisions : E 1 · IATA : - (SP A197 \leq 5 |/kg)

Hazard label(s): 9 / N

14.4 Packing group

TTT

14.5 Environmental hazards

Land transport (ADR/RID): Yes **Sea transport (IMDG):** Yes (P)

Air transport (ICAO-TI / IATA-DGR): Yes

14.6 Special precautions for user

None

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Authorisations

not applicable

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no.: 3, 75

Other regulations (EU)

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: None

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

E2 Hazardous to the aquatic environment in Category Chronic 2

Labelling for contents according to regulation (EC) No. 648/2004

not applicable

National regulations

Water hazard class

Classification according to AwSV - Class: 2 (Obviously hazardous to water)

15.2 Chemical Safety Assessment

Mixture: This information is not available.

SECTION 16: Other information

16.1 Indication of changes



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - RESIN

Revision Date: 05.08.2024 Revision: 1 Supersedes Date: N/A

Page: 12 / 12

None

16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures) ADR : European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des merchandises dangereuses par route) AICS: Australian, Inventory of Chemical Substances ATE: Acute Toxicity Estimation BCF: Bio-concentration factor BOD: Biochemical oxygen demand Bw: Body weight CAS: Chemical Abstract Service CLP: Classification, labelling and Packaging CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction CSA: Chemical Safety Assessment CSR: Chemical Safety Report DIN: German Standards Institute / German industrial norm (Deutsches Institut für Normung / Deutsche Industrienorm) DNEL: Derived No Effect Level DSL: Canada, Domestic Substances List EC50: Effective Concentration 50% EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances IARC: International Agency for Research on Cancer IATA: International Air Transport Association IBC: Intermediate Bulk Container IECSC: Inventory of Existing Chemical Substances in China IMDG Code: International Maritime Dangerous Goods Code IMO: International Maritime Organization ISO: International Standards Organization IUCLID: International Uniform Chemical Information Database IUPAC: International Union for Pure Applied Chemistry KECI: Korea, Existing Chemical Inventory LC50: Lethal Concentration 50% LD50: Lethal Dose 50% LEV: Local exhaust ventilation LOAEL: Lowest Observed Adverse Effect Level OEL: Lowest observable effect level MAK: Treshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG) NDSL: Canada, Non-Domestic Substances List NIOSH: National Institute for Occupational Safety & Health NOAEC: No Observed Adverse Effect Concentration NOAEL: No observed adverse effect level NOEC: No Observed Effect Concentration NOEL: No Observed Effect Level NZIoC: New Zealand Inventory of Chemicals OECD: Organization for Economic Cooperation and Development OEL: Occupational Exposure Limit PBT: persistent, bioaccumulative, toxic PIC: Prior Informed Consent PICCS: Philipines Inventory of Commercial Chemical Substances PNEC: Predicted No Effect Concentration RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer) OSAR: Quantitative Structure Activity Relation STP: Sewage treatment plant SVHC: Substance of Very High Concern TLV: Threshold Limit Value TSCA: Toxic Substance Control Act TWA: Time Weighted Average UVCB: Unknown or Variable Compositon, Complex Reaction Products, and Biological Materials VOC: Volatile organic compounds vPvB: very persistent, very bioaccumulative

16.3 Key literature references and sources for data

None

^{16.4} Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Calculation method.

16.5 Relevant H- and EUH-phrases (Number and full text)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - HARDENER

Revision Date: 05.08.2024 Revision: 1

Supersedes Date: N/A

Page: 1 / 15

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

SuperCast™ - HARDENER

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses

Artwork and decorative applications.

1.3 Details of the supplier of the safety data sheet

Supplier: Eli-Chem Resins UK Ltd

212 Dunsfold Park Canada Avenue Cranleigh GU6 8GA (UK)

+44 (0)1483 266636 (09:00 - 17:00 Mon-Thur / 09:00 - 16:00 Fri)

sales@elichem.co.uk

1.4 Emergency telephone number

Emergency number: +44 (0)1483 266636 office hours only

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4; H302 - Acute toxicity (oral): Category 4; Harmful if swallowed.

Skin Corr. 1B; H314 - Skin corrosion/irritation: Category 1B; Causes severe skin burns and eye damage.

Eye Dam. 1; H318 - Serious eye damage/eye irritation: Category 1; Causes serious eye damage.

Skin Sens. 1; H317 - Skin sensitisation: Category 1; May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms





Corrosion (GHS05) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

3-aminomethyl-3,5,5-trimethylcyclohexylamine; cas no.: 2855-13-2

1,3-cyclohexanedimethanamine; cas no.: 2579-20-6

Hazard statements

H314 Causes severe skin burns and eye damage.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - HARDENER

Revision Date: 05.08.2024 Revision: 1

> Supersedes Date: N/A Page: 2 / 15

P310 Immediately call a POISON CENTER/doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Adverse human health effects and symptoms

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH:

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH:

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

 $3\text{-}AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE} \; ; \; REACH \; No. : 01\text{-}2119514687-32-xxxx} \; ; \; EC \; No. : 220\text{-}666-8; \; CAS \; No. \; INCOME \\ \text{AND } \; AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE} \; ; \; AMINOMETHYLCYCLOHEXYLAMINE} \; ; \; AMINOMETHYLCYCLOHEXYLAMINE} \; ; \; AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE} \; ; \; AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE} \; ; \; AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE} \; ; \; AMINOMETHYLCYCLOHEXYLAMINE} \; ; \; AMINOMETHYLCYCLOHEXYLAMINE} \; ; \; AMINOMETHYLCYCLOHEXYLAMINE} \; ; \; AMINOMETHYLCYCLOHEXYLAMINE} \; ; \; AMINOMETHYLCYCLOHEXYLAMINE \; ; \;$

: 2855-13-2

Weight fraction : \geq 20 - < 60 %

Classification 1272/2008 [CLP]: Skin Corr. 1B; H314 Eye Dam. 1; H318 Acute Tox. 4; H302 Skin Sens. 1A; H317

Specific Conc. Limits : Skin Sens. 1A; H317: $C \ge 0,001 \% \bullet (ATE - oral : 1030 \text{ mg/kg bw})$

BENZYL ALCOHOL; REACH No.: 01-2119492630-38-xxxx; EC No.: 202-859-9; CAS No.: 100-51-6

Weight fraction : \geq 25 - < 50 %

Classification 1272/2008 [CLP]: Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319

Specific Conc. Limits: (ATE - oral : 1620 mg/kg bw)

1,3-CYCLOHEXANEDIMETHANAMINE; REACH No.: 01-2119543741-41-xxxx; EC No.: 219-941-5; CAS No.: 2579-20-6

Weight fraction: < 5 %

Classification 1272/2008 [CLP] : Skin Corr. 1A; H314 Eye Dam. 1; H318 Acute Tox. 4; H302 Acute Tox. 4; H312

Aquatic Chronic 3; H412

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove contaminated, saturated clothing immediately. Wash thoroughly the body (shower or bath). Remove affected person from the danger area and lay down. Transport affected person in lying position, in case of shortness of breath in half-sitting position. Put victim at rest, cover with a blanket and keep warm. Do not leave affected person unattended.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - HARDENER

Revision Date: 05.08.2024 Revision: 1 Supersedes Date: N/A

Page: 3 / 15

respiration. Call a physician immediately.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. In case of skin reactions, consult a physician. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure. In case of skin irritation, consult a physician.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

Following ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Following inhalation Irritation to respiratory tract Pulmonary irritation

Following skin contact Causes severe burns. erythema (redness) May cause an allergic skin reaction.

After eye contact Causes serious eye damage.

Following ingestion Causes severe burns. Gastrointestinal complaints Abdominal pain If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. First Aid, decontamination, treatment of symptoms. Subsequent observance for pneumonia and lung oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Extinguishing powder alcohol resistant foam Water spray jet Water

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Nitrogen oxides (NOx) Carbon monoxide Carbon dioxide (CO2) Ammonia (NH3) Phenols

5.3 Advice for firefighters

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Use personal protection equipment. See protective measures under point 7 and 8.

For emergency responders

Use personal protection equipment. Provide adequate ventilation. Remove persons to safety. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - HARDENER

Revision Date: 05.08.2024 Revision: 1 Supersedes Date: N/A

Page: 4 / 15

6.3 Methods and material for containment and cleaning up

For containment

Cover drains. Stop leak if safe to do so. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Take up mechanically, placing in appropriate containers for disposal.

For cleaning up

Collect in closed and suitable containers for disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4 Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

It is recommended to design all work processes always so that the following is excluded: Inhalation of vapours or spray/mists Skin contact Eye contact

Wear personal protection equipment (refer to section 8). If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Measures to prevent fire

Keep away from sources of ignition - No smoking. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Environmental precautions

Shafts and sewers must be protected from entry of the product. Provide for retaining containers, e.g. floor pan without outflow.

Advices on general occupational hygiene

Working places should be designed to allow cleaning at any time. Floors, walls and other surfaces in the hazard area must be cleaned regularly. After use replace the closing cap immediately. Wash hands and face before breaks and after work and take a shower if necessary. Wash hands before eating, drinking or smoking. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Only use containers specifically approved for the substance/product. Protect containers against damage. Keep container tightly closed and in a well-ventilated place.

Packaging materials

Unsuitable container/equipment material: Copper Alloy, containing copper

Hints on joint storage

Storage class (TRGS 510): 8A

Keep away from

Acid Oxidizing agent

Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

BENZYL ALCOHOL; CAS No.: 100-51-6



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - HARDENER

Revision Date: 05.08.2024 Revision: 1

Supersedes Date: N/A

Page: 5 / 15

Peak limitation: 2 (I)
Remark: H, Y

Version:

DNEL-/PNEC-values

DNEL/DMEL

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; CAS No.: 2855-13-2

Limit value type : DNEL Consumer (systemic)

Exposure route: Oral
Exposure frequency: Long-term
Limit value: 0,526 mg/kg
Limit value type: DNEL worker (local)

Exposure route: Inhalation
Exposure frequency: Short-term
Limit value: 0,073 mg/m³
Limit value type: DNEL worker (local)
Exposure route: Inhalation

Exposure route: Inhalation
Exposure frequency: Long-term
Limit value: 0,073 mg/m³

BENZYL ALCOHOL; CAS No.: 100-51-6

Limit value type : DNEL Consumer (systemic)

Exposure route: Dermal
Exposure frequency: Short-term
Limit value: 28,5 mg/kg

Limit value type : DNEL Consumer (systemic)

Exposure route: Dermal
Exposure frequency: Long-term
Limit value: 5,7 mg/kg

Limit value type : DNEL Consumer (systemic)

Exposure route: Inhalation
Exposure frequency: Short-term
Limit value: 95,5 mg/m³

Limit value type : DNEL Consumer (systemic)

Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 19,1 mg/m³

Limit value type : DNEL Consumer (systemic)

Exposure route : Oral
Exposure frequency : Short-term
Limit value : 25 mg/kg

Limit value type : DNEL Consumer (systemic)

Exposure route: Oral
Exposure frequency: Long-term
Limit value: 5 mg/kg

Limit value type : DNEL worker (systemic)

Exposure route : Dermal
Exposure frequency : Short-term
Limit value : 47 mg/kg

Limit value type : DNEL worker (systemic)

Exposure route: Dermal
Exposure frequency: Long-term
Limit value: 9,5 mg/kg

Limit value type : DNEL worker (systemic)

 $\begin{array}{lll} \mbox{Exposure route}: & \mbox{Inhalation} \\ \mbox{Exposure frequency}: & \mbox{Short-term} \\ \mbox{Limit value}: & \mbox{450 mg/m}^3 \end{array}$



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - HARDENER

Revision Date: 05.08.2024 Revision: 1

Supersedes Date: N/A

Page: 6 / 15

Limit value type : DNEL worker (systemic)

Exposure route: Inhalation
Exposure frequency: Long-term
Limit value: 5 mg/kg

PNEC

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; CAS No.: 2855-13-2

Limit value type : PNEC (Aquatic, freshwater)

Limit value: 0.06 mg/l

Limit value type : PNEC (Aquatic, intermittent release)

Limit value: 0,23 mg/l

Limit value type : PNEC (Aquatic, marine water)

Limit value : 0,006 mg/l

Limit value type : PNEC (Sediment, freshwater)

Limit value : 5,784 mg/kg

Limit value type : PNEC (Sediment, marine water)

Limit value : 0,578 mg/kg
Limit value type : PNEC (Soil)
Limit value : 1,121 mg/kg

Limit value type : PNEC (Sewage treatment plant)

Limit value : 3,18 mg/l

BENZYL ALCOHOL; CAS No.: 100-51-6

Limit value type : PNEC (Aquatic, freshwater)

Limit value : 1 mg/l

Limit value type : PNEC (Aquatic, intermittent release)

Limit value : 2,3 mg/l

Limit value type : PNEC (Aquatic, marine water)

Limit value : 0,1 mg/l

Limit value type : PNEC (Sediment, freshwater)

Limit value : 5,27 mg/kg

Limit value type : PNEC (Sediment, marine water)

Limit value : 0,527 mg/kg
Limit value type : PNEC (Soil)
Limit value : 0,456 mg/kg

Limit value type : PNEC (Sewage treatment plant)

Limit value : 39 mg/l

8.2 Exposure controls

Appropriate engineering controls

Provide for sufficient ventilation. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Technical measures and the application of suitable work processes have priority over personal protection equipment.

Personal protection equipment

Eye/face protection

Suitable eye protection

Eye glasses with side protection DIN-/EN-Norms: EN 166

Provide eye shower and label its location conspicuously

Skin protection

Hand protection

Suitable gloves type : Gloves with long cuffs

Suitable material: NBR (Nitrile rubber) PVC (polyvinyl chloride) CR (polychloroprene, chloroprene rubber) Butyl

caoutchouc (butyl rubber) FKM (fluoro rubber)

Wearing time with occasional contact (splashes) : > 60 min

Wearing time with permanent contact : > 480 min

Remark: When handling with chemical substances, protective gloves must be worn with the CE-label including the



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - HARDENER

Revision Date: 05.08.2024 Revision: 1 Supersedes Date: N/A

DIN-cup 4 mm

Page: 7 / 15

four control digits.

Breakthrough times and swelling properties of the material must be taken into consideration.

Tested protective gloves must be worn

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

DIN-/EN-Norms: EN ISO 374

Body protection

Suitable protective clothing

Remark: DIN-/EN-Norms

Protective clothing. : EN 14605 footwear : EN ISO 20345

Breakthrough times and swelling properties of the material must be taken into consideration.

Only wear fitting, comfortable and clean protective clothing.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation insufficient exhaust

Suitable respiratory protection apparatus

Combination filtering device Filter type: A

EN 14387

Remark

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

General information

When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Wash contaminated clothing immediately. Wash hands before breaks and after work. Emergency shower installed

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Liquid
Colour: light yellow
Odour: Amines
Safety characteristics

Freezing point :	(1013 hPa)		No data available	
Initial boiling point and boiling	(1013 hPa)	>	200	°C
range:	(1015 111 d)		200	C
Decomposition temperature :	(1013 hPa)		No data available	
Flash point :		>	100	°C
Auto-ignition temperature :			No data available	
Lower explosion limit:			No data available	
Upper explosion limit :			No data available	
Vapour pressure :	(50 °C)		not determined	
Density:	(25 °C)		1,05	g/cm³
Relative density :	(20 °C)		No data available	
Water solubility:	(20 °C)		No data available	
pH:	(20 °C / 10 g/l)		No data available	
log P O/W:			No data available	
Flow time :	(20 °C)		No data available	
Management	(25.00)		2500	D - * -

Viscosity: (25 °C) approx. 2500 mPa*s

Odour threshold:

Relative vapour density:

(20 °C)

No data available
No data available



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - HARDENER

Revision Date: 05.08.2024 Revision: 1

Supersedes Date: N/A

Page: 8 / 15

Flammable solids : Not applicable. **Flammable gases :** Not applicable.

9.2 Other information

partially miscible : Water **Other safety characteristics**

Evaporation rate
No data available
Miscibility
No data available

ConductivityNo data available

SECTION 10: Stability and reactivity

10.1 Reactivity

The product is stable under storage at normal ambient temperatures.

10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

Violent reaction with: Oxidising agent, strong. Strong acid

10.4 Conditions to avoid

Keep away from heat.

10.5 Incompatible materials

Oxidising agent, strong. Strong acid

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Acute oral toxicity

Parameter: LD50 (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; CAS No.: 2855-13-2)

Exposure route: Oral
Species: Rat
Effective dose: 1030 mg/kg
Method: OECD 401

Parameter: LC50 (BENZYL ALCOHOL; CAS No.: 100-51-6)

Exposure route: Oral
Species: Rat
Effective dose: 1620 mg/kg

Parameter: LD50 (1,3-CYCLOHEXANEDIMETHANAMINE; CAS No.: 2579-20-6)

Exposure route: Oral
Species: Rat
Effective dose: 700 mg/kg
Method: OECD 401

Acute dermal toxicity

Parameter: LD50 (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; CAS No.: 2855-13-2)

Exposure route : Dermal Species : Rat



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - HARDENER

Revision Date: 05.08.2024 Revision: 1 Supersedes Date: N/A

Page: 9 / 15

Effective dose : > 2000 mg/kg Method : OECD 402

Parameter: LD50 (1,3-CYCLOHEXANEDIMETHANAMINE; CAS No.: 2579-20-6)

Exposure route: Dermal
Species: Rat
Effective dose: 1700 mg/kg
Method: OECD 402

Acute inhalation toxicity

Parameter: LC50 (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; CAS No.: 2855-13-2)

Exposure route: Inhalation
Species: Rat
Effective dose: > 5,01 mg/l
Exposure time: 4 h
Method: OECD 403

Parameter: LC50 (BENZYL ALCOHOL; CAS No.: 100-51-6)

Exposure route: Inhalation (vapour)

Effective dose : 11 mg/l
Exposure time : 4 h
Method : Calculated

Parameter: LC50 (BENZYL ALCOHOL; CAS No.: 100-51-6)

Exposure route: Inhalation (dust/mist)

Species: Rat

Effective dose: > 4178 mg/m³

Exposure time: 4 h
Method: OECD 403

Corrosion

Product characteristics: Causes severe skin burns and eye damage.

Skin corrosion/irritation

Parameter: Skin corrosion/irritation (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE;

CAS No.: 2855-13-2)

Species: Rabbit
Result: Corrosive
Method: OECD 404

Parameter: Skin corrosion/irritation (BENZYL ALCOHOL; CAS No.: 100-51-6)

Species: Rabbit
Result: Irritant
Method: OECD 404

Product characteristics : corrosive

Serious eye damage/eye irritation

Parameter: Serious eye damage/eye irritation (3-AMINOMETHYL-3,5,5-

TRIMETHYLCYCLOHEXYLAMINE; CAS No.: 2855-13-2)

Species: Rabbit

Result : Causes serious eye damage

Method: OECD 405

Parameter : Serious eye damage/eye irritation (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Species: Rabbit
Result: slightly irritant
Method: OECD 405
Product characteristics: Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Parameter: Skin sensitisation (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; CAS No.:

2855-13-2)

Species: Guinea pig



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - HARDENER

Revision Date: 05.08.2024 Revision: 1

> Supersedes Date: N/A Page: 10 / 15

Result : Sensitising. Strong sensitiser (Subcategory 1A).

Method: OECD 406

Parameter: Skin sensitisation (BENZYL ALCOHOL; CAS No.: 100-51-6)

Species: Guinea pig
Result: Not sensitising.
Method: OECD 406

Product characteristics: May cause an allergic skin reaction.

Sensitisation to the respiratory tract

No data available

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH:

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter: LC50 (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; CAS No.: 2855-13-2)

Species: Leuciscus idus (golden orfe)

Effective dose : 110 mg/l Exposure time : 96 h

Parameter: LC50 (BENZYL ALCOHOL; CAS No.: 100-51-6)
Species: Pimephales promelas (fathead minnow)

Effective dose : 460 mg/l Exposure time : 96 h

Parameter: LC50 (1,3-CYCLOHEXANEDIMETHANAMINE; CAS No.: 2579-20-6)

Species: Leuciscus idus (golden orfe)

Effective dose: 130 mg/l Exposure time: 96 h

Method: DIN 38412 / part 15

Acute (short-term) toxicity to crustacea

Parameter: EC50 (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; CAS No.: 2855-13-2)

Species: Daphnia magna (Big water flea)

Effective dose : 23 mg/l Exposure time : 48 h Method : OECD 202

Parameter: EC50 (BENZYL ALCOHOL; CAS No.: 100-51-6)

Species: Daphnia magna (Big water flea)



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - HARDENER

Revision Date: 05.08.2024 Revision: 1

Supersedes Date: N/A

Page: 11 / 15

Effective dose : 230 mg/l Exposure time : 48 h Method : OECD 202

Chronic (long-term) toxicity to aquatic invertebrate

Parameter: NOEC (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; CAS No.: 2855-13-2)

Species: Daphnia magna (Big water flea)

Effective dose: 3 mg/l
Exposure time: 21 day(s)
Method: OECD 202

Parameter: NOEC (BENZYL ALCOHOL; CAS No.: 100-51-6)

Species: Daphnia magna (Big water flea)

Effective dose : 51 mg/l
Exposure time : 21 day(s)
Method : OECD 211

Acute (short-term) toxicity to algae and cyanobacteria

Parameter: ErC50 (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; CAS No.: 2855-13-2)

Species: Scenedesmus subspicatus

Effective dose: > 50 mg/l Exposure time: 72 h

Parameter: IC50 (BENZYL ALCOHOL; CAS No.: 100-51-6)

Species: Pseudokirchneriella subcapitata

Effective dose: 700 mg/l Method: OECD 201

Chronic (long-term) toxicity to aquatic algae and cyanobacteria

Parameter: NOEC (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; CAS No.: 2855-13-2)

Species: Scenedesmus subspicatus

Effective dose: 1,5 mg/l Exposure time: 72 h

Toxicity to microorganisms

Parameter: EC10 (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; CAS No.: 2855-13-2)

Species: Pseudomonas putida

Effective dose : 1120 mg/l Exposure time : 18 h

Parameter: EC50 (BENZYL ALCOHOL; CAS No.: 100-51-6)

Effective dose : 390 mg/l Exposure time : 24 h

Parameter: EC50 (1,3-CYCLOHEXANEDIMETHANAMINE; CAS No.: 2579-20-6)

Species: Pseudomonas putida

Effective dose: 90 mg/l

12.2 Persistence and degradability

Biodegradation

Parameter: Biodegradation (3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; CAS No.:

2855-13-2)

Degradation rate : 8 %

Evaluation: Not readily biodegradable (according to OECD criteria)

Parameter: Biodegradation (BENZYL ALCOHOL; CAS No.: 100-51-6)

Degradation rate: 95 %
Method: OECD 301A

Parameter : Biodegradation (BENZYL ALCOHOL ; CAS No. : 100-51-6)

Degradation rate : 92 %

Evaluation : Readily biodegradable (according to OECD criteria).

Method: OECD 302C



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - HARDENER

Revision Date: 05.08.2024 Revision: 1

Supersedes Date: N/A Page: 12 / 15

12.3 Bioaccumulative potential

Parameter: Bioconcentration factor (BCF) (BENZYL ALCOHOL; CAS No.: 100-51-6)

Value : 1,37

Parameter: Partition coefficient n-octanol/water (log value) (3-AMINOMETHYL-3,5,5-

TRIMETHYLCYCLOHEXYLAMINE; CAS No.: 2855-13-2)

Value: 0,99 logPow

Parameter: Partition coefficient n-octanol/water (log value) (BENZYL ALCOHOL; CAS No.: 100-51-6)

Value: 1,05 logPow

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH:

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of waste according to applicable legislation. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Collect the waste separately. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

14.1 UN number or ID number

UN 2735

14.2 UN proper shipping name

Land transport (ADR/RID)

AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE · 1,3-CYCLOHEXANEDIMETHANAMINE)

Sea transport (IMDG)

 $AMINES, LIQUID, CORROSIVE, N.O.S. \quad (ISOPHORONEDIAMINE \cdot 1, 3-CYCLOHEXANEDIMETHANAMINE)$

Air transport (ICAO-TI / IATA-DGR)

AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE 1,3-CYCLOHEXANEDIMETHANAMINE)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es): 8
Classification code: C7
Hazard identification number (Kemler
No.): 80
Tunnel restriction code: E
Special Provisions: LQ 1 | E 2
Hazard label(s): 8

Sea transport (IMDG)

Class(es): 8 **EmS-No.:** F-A / S-B



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - HARDENER

Revision Date: 05.08.2024 Revision: 1

> Supersedes Date: N/A Page: 13 / 15

Special Provisions : LQ 1 | · E 2 · IMDG-Code segregation group 18 - Alkalis

Hazard label(s):

Air transport (ICAO-TI / IATA-DGR)
Class(es): 8
Special Provisions: E 2
Hazard label(s): 8

14.4 Packing group

Π

14.5 Environmental hazards

Land transport (ADR/RID): No Sea transport (IMDG): No

Air transport (ICAO-TI / IATA-DGR): No

14.6 Special precautions for user

Warning: corrosive.

14.7 Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Authorisations

not applicable

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no.: 3, 75

Restrictions of occupation

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations (EU)

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: None

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

This product is not classified according to Directive 2012/18/EU.

Labelling for contents according to regulation (EC) No. 648/2004

not applicable

National regulations

Water hazard class

Classification according to AwSV - Class: 2 (Obviously hazardous to water)

Additional information

Substance/product listed in the following inventories (All components are listed or exempted).

- TSCA
- EINECS/ELINCS/NLP
- DSL/NDSL
- AICS



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - HARDENER

Revision Date: 05.08.2024 Revision: 1 Supersedes Date: N/A

Page: 14 / 15

- KECI
- PICCS
- IECSC
- NZIoC

15.2 Chemical Safety Assessment

Mixture: This information is not available.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures) ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des merchandises dangereuses par route) AICS: Australian, Inventory of Chemical Substances ATE: Acute Toxicity Estimation BCF: Bio-concentration factor BOD: Biochemical oxygen demand Bw: Body weight CAS: Chemical Abstract Service CLP: Classification, labelling and Packaging CMR: Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction CSA: Chemical Safety Assessment CSR: Chemical Safety Report DIN: German Standards Institute / German industrial norm (Deutsches Institut für Normung / Deutsche Industrienorm) DNEL: Derived No Effect Level DSL: Canada, Domestic Substances List EC50: Effective Concentration 50% EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances IARC: International Agency for Research on Cancer IATA: International Air Transport Association IBC: Intermediate Bulk Container IECSC: Inventory of Existing Chemical Substances in China IMDG Code: International Maritime Dangerous Goods Code IMO: International Maritime Organization ISO: International Standards Organization IUCLID: International Uniform Chemical Information Database IUPAC: International Union for Pure Applied Chemistry KECI: Korea, Existing Chemical Inventory LC50: Lethal Concentration 50% LD50: Lethal Dose 50% LEV: Local exhaust ventilation LOAEL: Lowest Observed Adverse Effect Level OEL: Lowest observable effect level MAK: Treshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG) NDSL: Canada, Non-Domestic Substances List NIOSH: National Institute for Occupational Safety & Health NOAEC: No Observed Adverse Effect Concentration NOAEL: No observed adverse effect level NOEC: No Observed Effect Concentration NOEL: No Observed Effect Level NZIoC: New Zealand Inventory of Chemicals OECD: Organization for Economic Cooperation and Development OEL: Occupational Exposure Limit PBT: persistent, bioaccumulative, toxic PIC: Prior Informed Consent PICCS: Philipines Inventory of Commercial Chemical Substances PNEC: Predicted No Effect Concentration RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer) QSAR: Quantitative Structure Activity Relation STP: Sewage treatment plant SVHC: Substance of Very High Concern TLV: Threshold Limit Value TSCA: Toxic Substance Control Act TWA: Time Weighted Average UVCB: Unknown or Variable Compositon, Complex Reaction Products, and Biological Materials VOC: Volatile organic compounds vPvB: very persistent, very bioaccumulative

16.3 Key literature references and sources for data

None

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Calculation method.

16.5 Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eve irritation.



according to Regulation (EC) No. 1907/2006 (REACH)

SuperCast™ - HARDENER

Revision Date: 05.08.2024 Revision: 1

> Supersedes Date: N/A Page: 15 / 15

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.